# Statistical Analysis of Threshing Characteristics of Impact-type Rice Plant Threshing Device

Choe, Jung Seob Department of Precision Mechanical Engineering, Kyungpook National University

Inoue, Eiji Department of Bioproduction Environmental Science, Graduate School of Kyushu University

Mitsuoka, Muneshi Department of Bioproduction Environmental Science, Graduate School of Kyushu University

Okayasu, Takashi Department of Bioproduction Environmental Science, Graduate School of Kyushu University

他

https://doi.org/10.5109/26163

出版情報:九州大学大学院農学研究院紀要. 58(1), pp.69-78, 2013-02. Faculty of Agriculture, Kyushu University バージョン: 権利関係:

## Statistical Analysis of Threshing Characteristics of Impact-type Rice Plant Threshing Device

## Jung Seob CHOE<sup>1</sup>, Eiji INOUE<sup>2</sup>, Muneshi MITUSOKA<sup>2</sup>\*, Takashi OKAYASU<sup>2</sup> and Yasumaru HIRAI<sup>2</sup>

(Received October 31, 2012 and accepted November 8, 2012)

An impact-type threshing device that applies perpendicular force to rice ear was developed in this study. Threshing experiment was performed for a single ear and to a bundle of rice plants. Crop properties and collision conditions were used as input parameters in this experiment to perform multiple regression analysis, thereby estimating threshing rate and percentage of grains with rachis branch. Optimal regression model for estimating threshing rate and percentage of grains with rachis branch was obtained for both single ear and bundle of rice plants. Although all four regression models had low analytical error and verification error, but relative error was high due to insufficient number of datasets and accuracy was low as a result. However, certain extent of estimation was possible for threshing rate. Observing that threshing rate was highly correlated with transverse threshing force and transverse displacement, it was inferred that threshing of rice plant by impact-type threshing device is from perpendicular force acting on rice ears. Although estimation of percentage of grains with rachis branch had low absolute error, accuracy was low because of relative error that is enlarged due to low rate of occurrence. Since percentage of grains with rachis branch was negatively correlated with net's mesh size, we concluded that the mesh size must be made as low as possible to reduce percentage of grains with rachis branch.

**Key words**: impact–type threshing device, multiple regression analysis, percentage of grains with rachis branch, threshing rate

## INTRODUCTION

Agricultural population in Korea and Japan is significantly declining each year, with concurrent increase in the ratio of aged population. Accordingly, number of farming houses will rapidly decrease, actually leading to enlarged farming size and heightened demand for large and highly efficient agricultural machinery. Head feed combine, which was developed in Japan as a rice plant harvester, has increased in size and efficiency over the years and has achieved significant improvement. However, its threshing and selection functions are still not satisfactory.

Head feed combine differs from common combine; common combine draws all cut crops into the threshing drum for threshing, while head feed combine transfers the rice plant stems cut from the cutting part by carrier chain and supplies only 40 cm from the tip of the rice ear to the threshing part, thereby lowering threshing energy and increasing selection efficiency.

However, longitudinal threshing by strike from threshing teeth, which has been used since development of head feed combine, creates many straws and makes selection difficult (Umeda Mikio, 1992 (Part 1, 2)). This leads to significant amount of grain loss. Also, strong striking force during threshing damages the rice grain. These factors necessitate an improvement in the threshing method.

In addition, the bottleneck in developing high-effi-

ciency head feed combine by increasing cutting width or accelerating speed is the limitation in the selection performance (Umeda Mikio, 1992 (Part 3, 4)). Because selection performance is directly connected to threshing method, fundamental improvement in threshing method is even more direly needed.

We based our study on the finding from previous studies, which discovered that threshing by applying a force perpendicular to the rachis branch of a rice plant requires only half of the magnitude required in the longitudinal direction (Inoue E. *et al.*, 2003) (Lee S. W. and Y. K. Huh, 1989) (Suastawa I. N. *et al.*, 1996). The final goal in our study was to change the current threshing method that strikes paddies along the length of the rice plant to threshing in the perpendicular direction. As the first step, we manufactured impact-type threshing device that applies perpendicular force to rice ear. Threshing experiment was performed for a single rice ear without leaves and a bundle of 5 rice ears, with different net mesh sizes, collision speeds, etc., and threshing performances were evaluated.

Also, to estimate threshing rate and percentage of grains with rachis branch, multiple regression analysis was performed using grain properties and collision conditions as input parameters. From results of multiple regression analysis, effect of grain properties and collision conditions on threshing rate and percentage of grains with rachis branch was analyzed.

## MATERIALS AND METHODS

## **Measurement of threshing force and displacement** *Measurement of threshing force*

Threshing force was measured for Hinohikari rice

<sup>&</sup>lt;sup>1</sup> Department of Precision Mechanical Engineering, Kyungpook National University, Korea

<sup>&</sup>lt;sup>2</sup> Department of Bioproduction Environmental Science, Graduate School of Kyushu University, Japan

<sup>\*</sup> Corresponding author (E-mail: mitsuoka@bpes.kyushu-u.ac.jp)

plant grown in an artificial field at the Hakozaki campus of Kyushu University, Japan, using a tensile tester as in Fig. 1. First, rice grain and primary rachis branch were fixed with a stand and a clamp, and the moving part was moved downward at constant speed to stretch a small rachis branch. Tensile speed was 0.50 mm/s and branch was about 10 mm. Threshing force was measured using a small load cell (TOYO, TI, 1000120) from the start of movement by the moving part until the grain was expelled from the small rachis branch. Data was recorded using a data recorder (TEAC), and the maximum tensile force was set to be the threshing force.

Fig. 2 shows the method for fixing the grain and rachis branch in longitudinal and perpendicular direction when measuring threshing force. When measuring longitudinal threshing force, end of the primary rachis branch was fixed to the stand and the grain was fixed to the clamp. For measurement of perpendicular threshing force, the grain was fixed to the clamp on the stand side and the primary rachis branch was fixed to the clamp on the load cell side. When fixing the grain with a clamp, length of the clamp was made parallel to the length of the



Fig. 1. Tensile tester.



Fig. 2. Method for fixing an ear.



Fig. 3. Position of threshing force.

grain (Ichikawa Tomohiko and Takao Sugiyama, 1994).

Because threshing force differs for different parts of the ear, a grain from predetermined position in each ear was used for measurement to minimize the effect of measurement site. As shown in Fig. 3, ear was divided into the upper, middle, and lower part. One primary rachis branch was selected from each position, and this branch in turn was divided into external, middle, and inner part. Threshing force was measured for grains from each of these positions.

#### Threshing displacement

Generally at the start of a tensile test, predetermined initial load is applied while fibers are fully stretched but not elongated. It was assumed that tension between the grain and small rachis branch should also be defined for initial state in which the fibers between the grain and the small rachis branch are fully stretched but not elongated. Therefore, we referred to fiber tensile test method of JIS for the method for calculating displacement until the threshing.

According to the chemical fiber stability test in JIS– L1050 (1992), "draw initial load–displacement curve as in Fig. 4. Find the point A at which angle of the tangent line is maximum, and then designate the intersection of that tangent line with x–axis as point T. Finally, set the point with x–coordinate of point T as point  $F_0$ , whose y–coordinate is the initial load."

Meanwhile, an example of load-displacement curve that is obtained in measurement of threshing force is shown in Fig. 5. When moving part of the tensile tester elongates the fibers between the grain and the small rachis branch, tensile force (load) increases with displacement until threshing, at which point the load also disappears. As in the chemical fiber stability test in JIS-



Fig. 4. Method for determining initial load in JISL1050 (1992).



Fig. 5. Threshing load-rachis branch displacement.

L1050 (1992), tangent line was drawn from the point A' of maximum load change. The point of intersection between the tangent line and displacement axis was set as point T'. A perpendicular line starting from T' was drawn, and intersection of the line with load–displacement curve was designated as  $F_0$ '. Load corresponding to  $F_0$ ' was set as the initial load. However, actual measured values include slight variability, and initial load was determined not for displacement of 0 mm but 1.5 mm as in Fig. 5.

## Threshing experiment using impact-type threshing device

An impact-type threshing device that can collide the net in the perpendicular direction of the rice ear was developed. Threshing experiment was performed for a single rice ear without leaves and a bundle of 5 rice ears with different net mesh sizes and collision speeds.

#### Experimental apparatus

In order to apply only perpendicular force to the rice ear, the device was designed such that the ear was not fixed and hung at about 30 cm from the end of the ear, and the ear would move with the net after collision. Steel bars with 2.0 mm diameter were placed equidistant in the net, as in Fig. 6. Interval between steel bars was set to 8, 10, 12, and 14 mm. Movement speed of the net can



Fig. 6. Impact-type threshing device (threshing net).



Fig. 7. Collision test equipment.

be controlled from  $0 \sim 17$  m/s in continuous interval. For measurement of collision speed, reflection tapes were attached in horizontal direction in 10 cm intervals on the net table and a light sensor was used to measure pulse interval when the net passes. From the pulse intervals, average speed between each reflection tapes was calculated. Collision speed was defined as average speed between 10 cm before collision to 10 cm after collision. Configuration of experimental apparatus is as in Fig. 7.

#### Experimental procedure

Threshing force and displacement in longitudinal and transverse direction for rice grain at designated location were measured 5 times for each condition to obtain the average values before performing the impact test.

In the single–ear threshing experiment, number of grains and chaffs to be used were counted before the experiment. For 5–ear bundle experiment, weight of the ears was measured, and then the net was collided into the ears. At this time, high–speed camera was used to capture images of threshing and scattering of grains, and light sensor was used to measure speed of the net. Next, grains were collected and grains threshed, grains with unthreshed head, and grains with rachis branch were counted or weighed. This process was repeated at maximum 6 times, and then grains and chaffs left on the ears were counted or weighed.

Due to limitations of experimental material and methods, number of data collected was insufficient. 32 datasets were collected for single–ear experiment and 17 datasets were collected for bundle experiment for regression analysis.

#### Multiple regression analysis

Grain properties and collision conditions from the threshing experiment by impact-type threshing device were used as input parameters in this experiment to perform multiple regression analysis, thereby estimating threshing rate and percentage of grains with rachis branch. Also, effect of crop properties and collision parameters on threshing rate and percentage of grains with rachis branch was evaluated using multiple regression results.

Multiple regression analysis uses multiple explanatory variables to predict a single target variable. It can be used to measure the extent of effect from each explanatory variable on the target variable (Ueda Taichiro *et al.*, 2004). In this study, multiple regression analysis was performed in order to predict threshing rate and percentage of grains with rachis branch from multiple crop properties and collision conditions. 26 datasets from total of 32 datasets was used for the regression analysis for single–ear experiment, and the other 6 datasets were used to verify accuracy of prediction by the multiple regression prediction equation. For the bundle experiment, 14 datasets were used for analysis and 3 datasets were used for verification.

Threshing rate and percentage of grains with rachis branch were set as target variables (non-explanatory variables). Total of 7 explanatory variables were used, including 5 crop properties and 2 collision conditions. The crop properties were: weight of a single grain (hereafter referred to as grain weight), longitudinal threshing force (along the length of the ear), longitudinal displacement, and perpendicular threshing force. The collision conditions were net's mesh size and net speed. In order to use crop properties and collision conditions as explanatory variables, it is necessary to check correlation between the target variables (threshing rate and percentage of grains with rachis branch) and these explanatory variables. For this purpose, we obtained correlation coefficient (r) between threshing rate or percentage of grains with rachis branch with crop properties or collision conditions and then performed two-tailed t-test using Eq. 1 at 5% significance level for determining crop properties and collision conditions to be used as explanatory variables.

$$t = \frac{|r|\sqrt{n-2}}{\sqrt{1-r^2}}$$
(1)

Also, explanatory variable selection criteria Ru, which can be obtained using Eq. 2, was used for determination of optimal model for multiple regression analysis(Makabe Hazime *et al.*, 1989).

$$Ru = 1 - (1 - R^2) \frac{n + k + 1}{n - k - 1}$$
(2)

R: multiple correlation n: number of data k: number of explanatory variables

Finally, mean of error in estimation obtained from inputting analysis data into the prediction equation of the optimal model compared to actual measurements (hereafter referred to as mean of analytical error) was obtained, as well as mean of error in estimation obtained from inputting verification data into the prediction equation compared to actual measurements (hereafter referred to as mean of verification error).

#### **RESULTS AND DISCUSSION**

## Threshing rate of single ear

Table 1 shows experimental results used for multiple regression analysis of threshing rate, and Table 2 shows correlation coefficients between crop properties or collision conditions with threshing rate obtained from the experimental results.

Variables shown to have significant correlation with threshing rate by Eq. 1 were longitudinal displacement, transverse threshing force, transverse threshing force, and net speed. Therefore, these 4 variables were used as explanatory variables in multiple regression analysis. The results are shown in Table 3.

Because p-value of longitudinal displacement was largest, multiple regression analysis was performed again only for the other 3 explanatory variables. For this analysis, p-value of transverse displacement was largest and multiple regression analysis was performed for the other 2 explanatory variables (Table 3).

Because the case with three explanatory variables had the largest Ru value, it was determined as the optimal regression model. Estimation value from the optimal model and actual measurements are shown in Fig. 8. Mean of analytical error was 5.52%, mean of verification error was 6.72%, and relative error was about 10%.

## Percentage of grains with rachis branch of single ear

Table 4 shows experimental results used for multiple

	Grain weight (g)	L. T– force (N)	L– disp. (mm)	T. T– force (N)	T– disp. (mm)	Net's mesh size (mm)	Net speed (m/s)	Threshing rate (%)
Analysis	2.617E-02	2.223	0.610	1.060	0.780	10	12.434	11.597
data	2.617E-02	2.223	0.610	1.060	0.780	10	13.854	15.314
	2.617E-02	2.223	0.610	1.060	0.780	10	15.240	22.058
	2.617E-02	2.223	0.610	1.060	0.780	10	16.550	29.378
	2.614E-02	2.258	0.686	1.168	0.782	12	17.229	36.951
	2.654E-02	2.252	0.734	1.042	0.839	10	17.008	38.503
	2.673E-02	2.057	0.650	0.925	0.723	10	16.256	42.214
	2.614E-02	2.258	0.686	1.168	0.782	10	17.008	42.743
	2.944E-02	1.431	0.629	0.376	0.642	10	11.868	42.815
	2.666E-02	1.952	0.659	1.036	0.710	10	16.262	46.398
	2.944E-02	1.431	0.629	0.376	0.642	10	13.137	48.554
	2.614E-02	2.258	0.686	1.168	0.782	8	17.022	50.052
	2.426E-02	2.591	0.592	0.824	0.627	10	16.314	51.001
	2.673E-02	2.057	0.650	0.925	0.723	12	16.221	51.510
	2.426E-02	2.591	0.592	0.824	0.627	12	16.315	52.037
	2.426E-02	2.591	0.592	0.824	0.627	14	16.289	53.387
	2.614E-02	2.258	0.686	1.168	0.782	14	17.077	60.573
	2.614E-02	2.258	0.686	1.168	0.782	10	19.344	62.090
	2.944E-02	1.431	0.629	0.376	0.642	10	16.601	63.751
	2.428E-02	2.742	0.540	0.702	0.593	10	16.072	65.302
	2.944E-02	1.431	0.629	0.376	0.642	10	15.002	68.389
	2.999E-02	1.431	0.629	0.376	0.642	10	15.002	68.668
	2.262E-02	1.921	0.488	0.721	0.503	10	16.124	72.639
	2.475E-02	2.223	0.475	0.694	0.581	10	16.635	76.535
	2.556E-02	2.062	0.488	0.476	0.503	10	16.339	82.546
	2.914E-02	1.635	0.530	0.463	0.617	10	17.008	84.101
Verification	2.614E-02	2.258	0.686	1.168	0.782	10	12.888	17.571
data	2.666E-02	1.952	0.659	1.036	0.710	12	16.137	35.851
	2.673E-02	2.057	0.650	0.925	0.723	10	16.256	44.441
	2.426E-02	2.591	0.592	0.824	0.627	8	16.370	53.639
	2.428E-02	2.742	0.420	0.702	0.484	10	16.072	67.129
	2.853E-02	1.205	0.473	0.316	0.590	10	17.008	78.718

 Table 1. Results of single-ear threshing rate experiment

'L.T-force' is 'Longitudinal threshing force' and 'L-disp.' is 'Longitudinal displacement',

'T.T–force' is 'Transverse threshing force' and 'T–disp.' is 'Transverse displacement'.

Table 2. Correlation coefficients between threshing rate and crop properties or collision conditions in the single-ear experiment

Grain	Longitudinal	Longitudinal	Transverse	Transverse	Net's	Net
weight	Threshing force	displacement	Threshing force	displacement	mesh size	speed
0.052	-0.254	-0.482	-0.575	-0.721	3.000E-02	0.405

Table 3.	Results	of regression	analysis of	threshing rate in	the single-ear	experiment
----------	---------	---------------	-------------	-------------------	----------------	------------

Number of explanatory variab	bles		Parameter	t	P-value	Coefficient
4	Multiple Correlation, R Number of datasets Ru	0.93 26 0.80	Intercept Longitudinaldisplacement Transverse threshing force Transverse displacement	0.34 0.51 -3.32 -2.13	0.74 0.62 $4.0 \times 10^{-3}$ 0.04	7.88 23.52 –32.49 –98.30
			Net speed	6.83	$9.4 \times 10^{-7}$	7.76
3	Multiple Correlation, R Number of datasets Ru	0.93 26 0.81	Intercept Transverse threshing force Transverse displacement Net speed	0.37 -3.95 -3.05 7.39	$\begin{array}{c} 0.72 \\ 6.8 \times 10^{-4} \\ 5.9 \times 10^{-3} \\ 2.1 \times 10^{-7} \end{array}$	8.49 -34.83 -79.13 7.92
2	Multiple Correlation, R Number of datasets Ru	0.87 26 0.75	Intercept Transverse threshing force Net speed	-2.52 -8.69 7.48	0.02 1.0×10 <sup>-8</sup> 1.3×10 <sup>-7</sup>	-44.48 -55.79 8.91

regression analysis of percentage of grains with rachis branch, and Table 5 shows correlation coefficients between crop properties or collision conditions with per-



Fig. 8. Comparison of estimation and measurement of singleear threshing rate.

centage of grains with rachis branch obtained from the experimental results.

Variables shown to have significant correlation with percentage of grains with rachis branch by Eq. 1 were grain weight, longitudinal threshing force, transverse threshing force, and net mesh size. Therefore, these 4 variables were used as explanatory variables in multiple regression analysis. The results are shown in Table 6.

Because p-value of longitudinal threshing force was largest, multiple regression analysis was performed again only for the other 3 explanatory variables. For this analysis, p-value of transverse threshing force was largest and multiple regression analysis was performed for the other 2 explanatory variables (Table 6).

Because the case with three explanatory variables had the largest Ru value, it was determined as the optimal

Table 4. Results of single-ear experiment for percentage of grains with rachis branch

	Grain weight (g)	L. T– force (N)	L– disp. (mm)	T. T– force (N)	T– disp. (mm)	Net's mesh size (mm)	Net speed (m/s)	Threshing rate (%)
Analysis	2.944E-02	1.431	0.629	0.376	0.642	10	16.601	0.163
data	2.914E-02	1.635	0.530	0.463	0.617	10	17.008	0.231
	2.999E-02	1.431	0.629	0.376	0.642	10	15.002	0.375
	2.944E-02	1.431	0.629	0.376	0.642	10	13.137	0.603
	2.944E-02	1.431	0629	0.376	0.642	10	11.868	0.807
	2.853E-02	1.205	0.473	0.316	0.590	10	17.008	1.128
	2.556E-02	2.062	0.488	0.476	0.503	10	16.339	1.291
	2.428E-02	2.742	0.540	0.702	0.593	10	16.072	1.779
	2.673E-02	2.057	0.650	0.925	0.723	10	16.256	2.627
	2.614E-02	2.258	0.686	1.168	0.782	8	17.022	2.635
	2.614E-02	2.258	0.686	1.168	0.782	10	19.344	2.805
	2.617E-02	2.223	0.610	1.060	0.780	10	13.854	2.994
	2.614E-02	2.258	0.686	1.168	0.782	10	17.008	3.862
	2.428E-02	2.742	0.420	0.702	0.484	10	16.072	4.081
	2.666E-02	1.952	0.659	1.036	0.710	10	16.262	4.170
	2.614E-02	2.258	0.686	1.168	0.782	10	12.888	4.447
	2.673E-02	2.057	0.650	0.925	0.723	10	16.256	4.675
	2.614E-02	2.258	0.686	1.168	0.782	12	17.229	5.358
	2.617E-02	2.223	0.610	1.060	0.780	10	12.434	5.518
	2.262E-02	1.921	0.488	0.721	0.503	10	16.124	6.295
	2.426E-02	2.591	0.592	0.824	0.627	10	16.314	7.884
	2.617E-02	2.223	0.610	1.060	0.780	10	16.550	8.434
	2.614E-02	2.258	0.686	1.168	0.782	14	17.077	11.442
	2.673E-02	2.057	0.650	0.925	0.723	12	16.221	12.778
	2.666E-02	1.952	0.659	1.036	0.710	12	16.137	14.820
	2.426E-02	2.591	0.592	0.824	0.627	14	16.289	19.495
Verification	2.944E-02	1.431	0.629	0.376	0.642	10	15.002	0.546
data	2.475E-02	2.223	0.475	0.694	0.581	10	16.635	1.535
	2.654E-02	2.252	0.734	1.042	0.839	10	17.008	2.709
	2.426E-02	2.591	0.592	0.824	0.627	8	16.370	4.444
	2.617E-02	2.223	0.610	1.060	0.780	10	15.240	6.768
	2.426E-02	2.591	0.592	0.824	0.627	12	16.315	13.091

 Table 5. Correlation coefficients between percentage of grains with rachis branch and crop properties or collision conditions in the single–ear experiment

Grain	Longitudinal	Longitudinal	Transverse	Transverse	Net's	Net
weight	Threshing force	displacement	Threshing force	displacement	mesh size	speed
-0.465	0.439	0.178	0.440	0.173	0.779	0.151

Number of explanatory varia	ables	Parameter	t	P-value	Coefficient	
4	Multiple Correlation, R	0.87	Intercept	0.09	0.93	1.73
	Number of datasets	26	Grain weight	-1.75	0.09	-910.26
	Ru	0.63	Longitudinal Threshing force	-0.56	0.58	-1.47
			Transverse Threshing force	1.48	0.15	3.37
			Net's mesh size	6.29	$3.1 \times 10^{-6}$	2.65
3	Multiple Correlation, R	0.87	Intercept	-0.61	0.55	-6.58
	Number of datasets	26	Grain weight	-2.10	0.05	-686.99
	Ru	0.652	Transverse Threshing force	1.39	0.18	2.78
			Net's mesh size	6.36	$2.1 \times 10^{-6}$	2.63
2	Multiple Correlation, R	0.85	Intercept	0.08	0.94	0.77
	Number of datasets	26	Grain weight	-3.08	$5.2 \times 10^{-3}$	2.71
	Ru	0.649	Net's mesh size	6.47	$1.3 \times 10^{-6}$	-906.29

Table 6. Results of regression analysis of percentage of grains with rachis branch in the single-ear experiment

regression model. Estimation value from the optimal model and actual measurements are compared in Fig. 9. Mean of analytical error was 1.83% and mean of verification error was 2.29%, but relative error was about 70% and had low accuracy.



Fig. 9. Comparison of estimation and measurement of singleear percentage of grains with rachis branch.

Table 7. Results of bundle threshing rate experiment

## Threshing rate of bundle

Table 7 shows experimental results used for multiple regression analysis of bundle threshing rate, and Table 8 shows correlation coefficients between crop properties or collision conditions with threshing rate obtained from the experimental results.

Variables shown to have significant correlation with threshing rate by Eq. 1 were grain weight, longitudinal threshing force, longitudinal displacement, transverse threshing force, and transverse displacement. Therefore, these 5 variables were used as explanatory variables in multiple regression analysis. The results are shown in Table 9.

Because p-value of grain weight was largest, multiple regression analysis was performed again only for the other 4 explanatory variables. For this analysis, p-value of longitudinal threshing force was largest and multiple regression analysis was performed for the other 3 explanatory variables. Again, p-value of longitudinal displacement was largest and multiple regression analysis was performed for the other 2 explanatory variables (Table 9).

	Grain weight (g)	L. T– force (N)	L– disp. (mm)	T. T– force (N)	T– disp. (mm)	Net's mesh size (mm)	Net speed (m/s)	Threshing rate (%)
Analysis	2.681E-02	2.239	0.733	0.902	0.716	10	13.107	8.395
data	2.586E-02	2.261	0.803	0.961	0.742	10	17.392	24.110
	2.681E-02	2.239	0.733	0.902	0.716	8	17.229	27.080
	2.681E-02	2.239	0.733	0.902	0.716	12	17.242	30.499
	2.681E-02	2.239	0.733	0.902	0.716	14	17.288	36.330
	2.681E-02	2.239	0.733	0.902	0.716	10	20.072	43.182
	2.318E-02	1.559	0.459	0.357	0.538	10	17.468	66.811
	2.699E-02	1.312	0.451	0.361	0.579	10	17.483	73.512
	2.506E-02	1.217	0.475	0.298	0.542	10	17.438	79.836
	2.402E-02	1.350	0.423	0.319	0.604	8	17.053	84.449
	2.402E-02	1.350	0.423	0.319	0.604	12	17.080	85.517
	2.402E-02	1.350	0.423	0.319	0.604	10	17.453	86.242
	2.402E-02	1.350	0.423	0.319	0.604	14	17.257	89.945
	2.402E-02	1.350	0.423	0.319	0.604	10	19.325	92.579
Verification	2.681E-02	2.239	0.733	0.902	0.716	10	17.379	23.418
data	2.535E-02	2.654	0.654	0.839	0.681	10	17.258	46.561
	2.402E-02	1.350	0.423	0.319	0.604	10	12.888	72.519

Table 8. Correlation coefficients between bundle threshing rate and crop properties or collision conditions

Grain	Longitudinal	Longitudinal	Transverse	Transverse	Net's	Net
weight	Threshing force	displacement	Threshing force	displacement	mesh size	speed
-0.770	-0.948	-0.954	-0.952	-0.852	0.058	0.407

Table 9. Results of regression analysis of bundle threshing rate

Number of explanatory variable	es		Parameter	t	P-value	Coefficient
5	Multiple Correlation, R	0.97	Intercept	-0.45	0.66	-1413.46
	Number of datasets	14	Grain weight	0.45	0.66	19806.74
	Ru	0.84	Longitudinal Threshing force	0.45	0.66	383.56
			Longitudinal displacement	0.46	0.66	956.98
			Transverse Threshing force	-0.50	0.63	-1469.41
			Transverse displacement	0.58	0.58	945.68
4	Multiple Correlation, R	0.97	Intercept	-0.08	0.93	-13.23
	Number of datasets	14	Longitudinal Threshing force	0.07	0.95	3.82
	Ru	0.86	Longitudinal displacement	0.12	0.90	24.59
			Transverse Threshing force	-0.83	0.43	-164.01
			Transverse displacement	1.43	0.17	227.80
3	Multiple Correlation, R	0.97	Intercept	-0.05	0.96	-4.70
	Number of datasets	14	Longitudinal displacement	0.11	0.92	15.94
	Ru	0.88	Transverse Threshing force	-1.61	0.14	-152.35
			Transverse displacement	1.82	0.10	222.03
2	Multiple Correlation, R	0.97	Intercept	0.06	0.96	2.94
	Number of datasets	14	Transverse Threshing force	-5.84	$1.1 \times 10^{-4}$	-142.46
	Ru	0.90	Transverse displacement	2.14	0.06	215.38



Fig. 10. Comparison of estimation and measurement of singleear threshing rate.

Because explanatory variable 2 had the largest Ru value, it was determined as the optimal regression model. Estimation value from the optimal model and actual measurements are compared in Fig. 10. Accuracy was not high as mean of analytical error was 4.86%, mean of verification error was 12.26%, and relative error was about 25%.

## Percentage of grains with rachis branch of bundles

Table 10 shows experimental results used for multiple regression analysis of percentage of grains with rachis branch for bundles, and Table 11 shows correlation coefficients between crop properties or collision conditions with percentage of grains with rachis branch obtained from the experimental results. Variables shown to have significant correlation with percentage of grains with rachis branch by Eq. 1 were longitudinal displacement, transverse threshing force, and net mesh size. Therefore, these 3 variables were used as explanatory variables in multiple regression analysis. The results are shown in Table 12.

Because p-value of transverse threshing force was largest, multiple regression analysis was performed again only for the other 2 explanatory variables (Table 12).

Because explanatory variable 2 had the largest Ru value, it was determined as the optimal regression model. Estimation value from the optimal model and actual measurements are compared in Fig. 11. Mean of analytical error was 1.14% and mean of verification error was 0.78%, but occurrence of grains with rachis branch was low as in the single–ear experiment and the relative error was 80%, showing low accuracy.

26 datasets were used for single–ear and 14 datasets were used for bundle experiment for multiple regression analysis in this study, which is limited in reflecting characteristics of the population. However, estimation was possible to certain extent for threshing rate. Based on high correlation of threshing rate with transverse threshing force and transverse displacement, threshing of rice plant by impact–type threshing device can be thought to be from a force acting perpendicular to the rice ear.

Although estimation of percentage of grains with rachis branch had low absolute error, it is hard to expect high accuracy due to relative error that is increased by

	Grain weight (g)	L. T– force (N)	L– disp. (mm)	T. T– force (N)	T– disp. (mm)	Net's mesh size (mm)	Net speed (m/s)	Threshing rate (%)
Analysis	2.402E-02	1.350	0.423	0.319	0.604	10	19.325	0.251
data	2.402E-02	1.350	0.423	0.319	0.604	8	17.053	0.492
	2.402E-02	1.350	0.423	0.319	0.604	10	17.453	0.643
	2.402E-02	1.350	0.423	0.319	0.604	10	12.888	0.667
	2.506E-02	1.217	0.475	0.298	0.542	10	17.438	0.769
	2.681E-02	2.239	0.733	0.902	0.716	10	13.107	1.084
	2.681E-02	2.239	0.733	0.902	0.716	8	17.229	1.089
	2.402E-02	1.350	0.423	0.319	0.604	14	17.257	1.236
	2.402E-02	1.350	0.423	0.319	0.604	12	17.080	1.347
	2.318E-02	1.559	0.459	0.357	0.538	10	17.468	2.658
	2.535E-02	2.654	0.654	0.839	0.681	10	17.258	2.689
	2.681E-02	2.239	0.733	0.902	0.716	10	20.072	3.169
	2.586E-02	2.261	0.803	0.961	0.742	10	17.392	4.509
	2.681E-02	2.239	0.733	0.902	0.716	14	17.288	10.933
Verification	2.699E-02	1.312	0.451	0.361	0.579	10	17.379	0.509
data	2.681E-02	2.239	0.733	0.902	0.716	10	17.258	1.780
	2.681E-02	2.239	0.733	0.902	0.716	10	12.888	5.202

Table 10. Results of the bundle experiment for percentage of grains with rachis branch

 Table 11.
 Correlation coefficients between percentage of grains with rachis branch and crop properties or collision conditions in the bundle experiment

Grain	Longitudinal	Longitudinal	Transverse	Transverse	Net's	Net
weight	Threshing force	displacement	Threshing force	displacement	mesh size	speed
0.481	0.513	0.557	0.551	0.486	0.537	0.156

Table 12. Results of regression analysis of percentage of grains with rachis branch in the bundle experiment

Number of explanatory variables			Parameter	t	P-value	Coefficient
3	Multiple Correlation, R Number of datasets Ru	$0.80 \\ 14 \\ 0.35$	Intercept Longitudinal displacement Transverse Threshing force Net's mesh size	-1.96 0.63 -0.17 3.00	0.08 0.54 0.87 0.01	-13.96 14.29 -1.99 0.89
2	Multiple Correlation, R Number of datasets Ru	$0.80 \\ 14 \\ 0.44$	Intercept Longitudinal displacement Net's mesh size	-3.59 3.24 3.14	$4.2 \times 10^{-3}$ $7.9 \times 10^{-3}$ $9.5 \times 10^{-3}$	-12.94 10.52 0.89



**Fig. 11.** Comparison of estimation and measurement of bundles percentage of grains with rachis branch.

low rate of occurrence. Nonetheless, the rate was inversely correlated with net mesh size and it can be inferred that the mesh size of the impact–type threshing device should be made as small as possible to reduce percentage of grains with rachis branch.

## SUMMARY AND CONCLUSION

In this study, an impact-type threshing device that applies perpendicular force to rice ear was developed. Threshing experiment was performed for a single rice ear without leaves and a bundle of 5 rice ears, with different net mesh sizes, collision speeds, etc., and threshing performances were evaluated. From results from this experiment, crop properties and collision conditions were used as input parameters to multiple regression analysis in order to estimate threshing rate and percentage of grains with rachis branch. Also, from results of multiple regression analysis, effect of grain properties and collision conditions on threshing rate and percentage of grains with rachis branch was analyzed. Main results are as follows. 1. Longitudinal displacement, transverse threshing force, transverse displacement, and net speeds, which had statistically significant correlation with threshing rate of single ear, were used as explanatory variables in multiple regression analysis. The regression model expressed in terms of transverse threshing force, transverse displacement, and net speed, and excluding longitudinal displacement, was shown to be optimal. For this model, mean of analytical error was 5.52%, mean of verification error was 6.72%, and relative error was about 10%.

2. Grain weight, longitudinal threshing force, transverse threshing force, and net mesh size, which had statistically significant correlation with percentage of grains with rachis branch of single ear, were used as explanatory variables in multiple regression analysis. The regression model expressed in terms of grain weight, transverse threshing rate, and net mesh size, and excluding longitudinal threshing force, was shown to be optimal. For this model, mean of analytical error was 1.83% and mean of verification error was 2.29%. Although these errors were low, relative error was about 70% and the model's accuracy was low.

3. Grain weight, longitudinal threshing force, longitudinal displacement, transverse threshing force, and transverse displacement, which had statistically significant correlation with threshing rate of bundle, were used as explanatory variables in multiple regression analysis. The regression model expressed in terms of transverse threshing force and transverse displacement was shown to be optimal. This model had low accuracy as mean of analytical error was 4.86%, mean of verification error was 12.26%, and relative error was about 25%.

4. Longitudinal displacement, transverse threshing force, and net mesh size, which had statistically significant correlation with percentage of grains with rachis branch of bundles, were used as explanatory variables in multiple regression analysis. The regression model expressed in terms of longitudinal displacement and net mesh size, and excluding transverse threshing force, was shown to be optimal. Mean of analytical error was 1.14% and mean of verification error was 0.78%, but occurrence of grains with rachis branch was low as in the single–ear experiment and the relative error was 80%, showing low accuracy.

Number of datasets in this study may be insufficient in fully reflecting characteristics of the population, and accumulation of data is thought to be required in the future. Additionally, in order to expedite commercialization of impact-type threshing device, experiment should be performed for rice ears with leaves on them in order to collect data as close to the actual condition as possible. Also, threshing phenomenon should be understood in detail by taking into account interaction between grains. Such efforts will be needed to reduce various errors in estimating threshing phenomenon.

## ACKNOWLEDGEMENTS

This Research was supported by Kyungpook National University Research Fund, 2012.

#### REFERENCES

- Ichikawa Tomohiko and Takao Sugiyama 1994 Development of Testing Equipment for the Shattering Habit of Paddy (Part 1), Journal of the Japanese Society of Agricultural Machinery, 56(1): 101–107
- Inoue E., Ikuo Ueka, Yasumaru Hirai, Masami Matui, Takashi Fukushima and Ken Mori 2003 Evaluation of Strength Distribution on Detachment Force of Paddy Grain, *Sci. Bull. Fac. Agr., Kyushu Univ.*, **58**(1, 2): 27–32
- Lee S. W. and Y. K. Huh 1989 Threshing and Cutting Forces for Korean Rice, TRANSACTIONS of ASAE, 27(6): 1654–1657, 1660
- Makabe Hazime, Tetsuo Miyamura and Kazuaki Suzuki 1989 Sinraiseimoderuno toukeikaiseki, Kyoritsu Shuppan Co., Ltd.(Tokyo, Japan)
- Suastawa I. N., O. Kitani, N. Sakai, S. Yonekawa, T. Okamoto and T. Torii 1996 Grain Detachment Strength and Grain Mass of Three Rice Types. Journal of the Japanese Society of Agricultural Machinery, 58(1): 65–72
- Ueda Taichiro, Maki Kobayashi and Miki Fuchigami 2004 Exceldemanabukaikibunseki nyumon, Ohmsha, Ltd. (Tokyo, Japan)
- Umeda Mikio 1992 Analysis of Threshing Mechanism of Head Feeding Thresher (Part 1, 2, 3, 4), Journal of the Japanese Society of Agricultural Machinery, 54(1): 47–55, 54(2): 41–50, 54(3): 43–52, 54(4): 49–57