Consideration on the Influence of Seismic Shaking on Forest Slope Stability and Landslide Warning Rainfall in the Aftermath of the Strong Earthquake

Kubota, Tetsuya

Laboratory of Erosion Control, Division of Forest Environmental Sciences, Department of Agro-environmental Sciences, Faculty of Agriculture, Kyushu University

Nakamura, Go

Nagase Brothers Inc.

Shinohara, Yoshinori

Laboratory of Erosion Control, Division of Forest Environmental Sciences, Department of Agro-environmental Sciences, Faculty of Agriculture, Kyushu University

Adition, Aril

Laboratory of Erosion Control, Division of Forest Environmental Sciences, Department of Agro-environmental, Graduate School of Bioresource and Bioenvironmental Sciences, Kyushu University

<https://doi.org/10.5109/1434407>

出版情報：九州大学大学院農学研究院紀要. 59 (1), pp.163-167, 2014-02-28. Faculty of Agriculture, Kyushu University

バージョン：

権利関係：

Consideration on the Influence of Seismic Shaking on Forest Slope Stability and Landslide Warning Rainfall in the Aftermath of the Strong Earthquake

Tetsuya KUBOTA*, Go NAKAMURA¹, Yoshinori SHINOHARA and Aril ADITIAN²

Laboratory of Erosion Control, Division of Forest Environmental Sciences,
Department of Agro–environmental Sciences, Faculty of Agriculture,
Kyushu University, Fukuoka 812–8581, Japan

(Received October 31, 2013 and accepted November 11, 2013)

The research concerning about the warning rainfall criteria of landslides after strong earthquakes is conducted associated with the great earthquake in Eastern Japan in 2011 ($M=9.0$). After this kind of strong earthquake, soil strength of the slopes in the region that were exposed to the strong seismic forces is generally reduced by seismic shaking (vibration). In this situation, the revised rainfall criteria for landslides are required. On this point of view, the response of landslide to rainfall under this weaken soil condition was studied. Hence, the impact of rainfall events on the specific landslide slopes that experienced the strong seismic shaking is analyzed using numerical simulation method i.e. finite element method (FEM) in order to evaluate the critical rainfall threshold for landslide occurrence. Consequently, we obtained following results.

In the result of FEM analysis, the cracks induced by the earthquake are effective to increase the seepage and render the slopes instable. The slope deterioration mentioned above due to the impact of earthquake causes temporarily 40~50% reduction of critical rainfall for landslide occurrence, corresponding to decrease in safety factor “ F_s ” of the slopes from $F_s=1.02\sim1.04$ to $F_s=0.83\sim0.95$. This reduction rate of critical rainfall is at same level as in the earlier researches based on field observations.

Key words: earthquake, FEM, landslides, rainfall, slope stability

INTRODUCTION

The research on the warning critical rainfall threshold of landslides after strong earthquakes is conducted associated with the great earthquake in Eastern Japan in 2011 ($M=9.0$). After this kind of strong earthquake, soil strength of the slopes in the region that were exposed to the strong seismic forces are generally reduced by seismic shaking or vibration and disturbance with certain slope deformation (Abe, 2011). In this situation, the revised rainfall critical threshold for landslide occurrence are required.

On this point of view, we are intrigued to elucidate the response of landslide to rainfall under this weaken soil condition. Hence, the impact of rainfall events on the specific landslide slopes that experienced the strong seismic shaking is analyzed using numerical simulation method i.e. finite element method (FEM) in order to evaluate the critical rainfall threshold for landslide occurrence.

METHOD

Field investigation and geotechnical indoor test with samples collected from the landslide slopes (Figs. 1~5) are conducted to obtain the basic data for FEM analysis such as hydraulic conductivity “ k ” and soil shear strength at the slopes that experienced strong earthquake. Then,

Fig. 1. An example of landslide scarp induced by Earthquake in Shikanoshima (Granite).

Fig. 2. An example of landslide induced by Earthquake in Shikanoshima (Granite).

¹ Nagase Brothers Inc.

² Laboratory of Erosion Control, Division of Forest Environmental Sciences, Department of Agro–environmental, Graduate School of Bioresource and Bioenvironmental Sciences, Kyushu University

* Corresponding author (E–mail: kubot@agr.kyushu-u.ac.jp)

Fig. 3. An example of landslide in Shintate area (university forest, Schist).

Fig. 4. An example of landslide scarp in Shintate area (university forest, Schist).

Fig. 5. The whole view of a sample landslide in Shintate area (in university forest, Schist).

Fig. 6. An example of crack on the slope generated by an earthquake.

Fig. 7. The simple shear test machine.

Fig. 8. The mechanical shaker to give soil samples a shaking impact.

Fig. 9. The mechanical shear test of soil samples.

Fig. 10. An example of the FEM slope stability analysis on a disturbed slope by the earthquake (Shikanoshima, Shallow slide, Granite, maximum increment of the shear stress with tension crack at the slope top).

FEM analysis which combines rainfall seepage analysis and slope stability analysis with the rainfall data at nearest meteorological observatory is conducted under the earthquake impact i.e. the slope condition with cracks (Fig. 6) which are located at the top of the slope and have high “ k ” or reduced soil strength. Comparing the FEM results with ones without earthquake impact, the influence of the earthquake shaking to the landslide slopes is estimated.

Simultaneously, some soil samples of weathered schist were also prepared for shear tests with roots and without roots, to clarify the influence of seismic shaking on soil strength (Figs. 7~9). The seismic shaking was generated by mechanical shaker up to 1,500 gal.

In the result of FEM analysis (Figs. 10, 11, 12), the cracks induced by the earthquake play a great roll to increase the rainfall seepage effectively and render the slopes instable. Also, reduced soil strength such as 4% decrease in internal friction angle as its residue strength (Nagamine, 2009) due to the deformation in the slope stratum caused instability of the slope.

The slope deterioration mentioned above due to the impact of earthquake causes 40~50% reduction of critical rainfall threshold for landslide occurrence temporarily (Figs. 13, 14). It is corresponding to the decrease in the safety factor “ F_s ” of the slopes from 1.02~1.04 to F_s =0.83~0.95 (Figs. 13, 14). This reduction rate of critical rainfall mentioned above is as same level as ones in the

Fig. 11. An example of the FEM slope stability analysis on a disturbed slope by the earthquake (Shintate, Deep slide, Schist, with tension crack at the slope top).

The slope stability (factor of safety F_s) of the shallow landslide after earthquake

Fig. 12. The influence of cracks by the earthquake on the shallow landslide stability F_s .

The rainfall at the shallow landslide slope after the earthquake and slope stability F_s (Under the premise that the coefficient of permeability is fivefold of original one.)

Fig. 13. The influence of increase in hydraulic conductivity “ k ” at the shallow landslide.

former several researches.

However, the influence of the seismic shaking on soil strength obtained from the mechanical shear test (Itoh *et.al.*, 2013) is not obvious (Figs.15, 16). In Fig. 6, the cohesion C is bigger in the case with roots than the one without roots and tends to reduce after 1,500 gal earthquake shaking. On the other hand, the inner frictional angle ϕ is obviously increased after 1,500 gal earthquake shaking while the difference by the existence of roots could not be found.

Fig. 14. The influence of cracks and reduction in soil strength at the deep landslide.

Fig. 15. Influence of seismic shaking on the soil strength (cohesion C).

Fig. 16. Influence of seismic shaking on the soil strength (internal friction angle ϕ).

CONCLUSION

Consequently, the impact of giant earthquakes causes at most 50% reduction of the critical rain threshold (rainfall criteria) over which landslides may occur. It is quite large influence that we have to consider in the aftermath of strong earthquake.

The conclusion summary is given in followings.

- 1) In the result of FEM analysis, the cracks induced by the earthquake are effective to increase the seepage of rainfall and render the slopes instable.
- 2) The slope deterioration mentioned above due to the impact of earthquake causes temporarily 40~50% reduction of critical rainfall for landslide occurrence, corresponding to decrease in safety factor “Fs” of

the slopes from $F_s=1.02\sim1.04$ to $F_s=0.83\sim0.95$.

- 3) This reduction rate of critical rainfall is as same level as in the former researches based on field observations.
- 4) On the other aspect, the influence of the seismic shaking on soil strength obtained from “the mechanical shear test” is not obvious.

REFERENCES

- Abe, S. and T. Higaki 2011 Geological and geomorphological characteristics of landslides caused by the 2011 Off the Pacific Coast of Tohoku Earthquake. Proc. 50th Congress of Japan landslide society, pp. 3–4
- Hiramatsu, S., T. Mizuyama, Y. Ishikawa and S. Osanai 1999 Study on influence of cracks caused by earthquake on hillslope stability. *Journal of the Japan landslide society*, **36**(2): 3–12
- Itoh, Y., S. Hiramatsu, T. Fukuyama and T. Miyamae 2013 An experimental study on the slope stability in Granite region after earthquakes. Proc. 2013 Annual Congress of Japan society of erosion control engineering, A–pp. 56–57
- Jitosono, T., E. Shimokawa, M. Matsumoto and Y. Teramoto 1998 Distribution and topographical characteristics of slope failures caused by earthquakes in northwestern part of Kagoshima in 1997. *Journal of the Japan society of erosion control engineering*, **51**(1): 38–45
- Kubota, T. 2011 Impacts of the increased rain due to climate change on shallow landslides and sediment runoffs in Kyushu district, Japan. *Advances in geosciences*, World scientific publishing, **23**: 63–73
- Kubota, T. 2011 Landslide disasters in northern Kyushu area caused by strong rainfalls in July 2010 and the influence of the climate change. *Water Science*, Japan Chisan–Chisui association, No. 320: 85–99
- Kubota, T. and M. Matsui 2011 Elucidation of the influence of forest load on the landslide slope stability. Proc. 50th Congress of Japan landslide society, pp. 119–120
- Kubota, T. 2006 Landslide disasters by the Fukuoka earthquake in 2005. Proc. 3rd Congress on the sediment related disaster, JSCE West, pp. 1–6
- Kubota, T., H. Omura and Hasnawir 2006 The traveling distance analysis of landslides and its application to the risk management, land use restriction in Kyushu district, Japan. *Geophysical research abstracts, European geophysical society*, Vol. 8, 01893
- Kubota, T., P. Paudel and H. Omura 2006 The influence of forests on susceptibility factors for slope stability – Some typical case for shallow landslides in western Japan –. Proc. of the International conference on geotechnical engineering Singapore, pp. 111–118
- Kubota, T., H. Omura, M. Kaibori, O. Shimizu, T. Jitousono, H. Ochiai, T. Uchida, Y. Ishii and Y. Yasuda 2005 Landslide disasters triggered by the Fukuoka Seihou–Oki Earthquake on March 2005. *Journal of the Japan society of erosion control engineering*, **58**(2): 32–37
- Kubota, T., H. Omura, T. Okumura, Y. Tada and P. Paudel 2004 Effect of forest load on the slope stability with different forest types and various logging condition. *Journal of the Japan landslide society*, **41**(3): 57–65
- Kubota, T., H. Omura, K. Morita and T. Nagasawa 2002 Some features of landslides by the earthquake for risk assessment and mapping. *Geophysical research abstracts, European geophysical society*, vol. 4, EGS02–A–005
- Kubota, T. 2002 The occurrence situation of rock fall and rock failure caused by the Western Tottori Earthquake and an example of restored works. *Journal of the Japan landslide society*, **38**(4): 52–57
- Mizuyama, T., M. Kaibori, K. Matsumura, S. Tsuchiya, S. Hiramatsu, Y. Onda and H. Terada 2001 The sediment related disaster caused by the Geiyo Earthquake on March 24 in 2001. *Journal*

- of the Japan society of erosion control engineering, **54**(1): 98–99
- Nagamine, M., T. Yamamoto and I. Osaka 2009 Strength of landslide slope consisting of the Sangun metamorphic rocks in Yamaguchi prefecture by DEM-based landform analysis. *Journal of the Japan landslide society*, **46**(3): 43–48
- Nakashima, T., T. Fukazawa, T. Terakado, T. Yamada, Y. Ueno and M. Ura 2011 A report of earthquake induced landslides and road crossing diagonally. Proc. 50th Congress of Japan landslide society, pp. 7–8
- Cai, F., K. Ugai, M. Yamada, S. Goto and K. Higuchi 2011 Investigation report of Hanokidaira landslide in Shirakawa city, Fukushima prefecture induced by the Great East Japan Earthquake. Proc. 50th Congress of Japan landslide society, pp. 11–12
- Taniguchi, E., T. Kubota and T. Kuwabara 1986 The investigation report of Matsukoshi landslide induced by the Western Nagano Earthquake. *Civil engineering journal*, Public Works Research Center, **28**(1): 59–65
- Uchida, T., M. Yamada, S. Mori, M. Fujii and T. Kubota 2002 The occurrence of rock fall and rock failure caused by the Western Tottori Earthquake and an example of restored works. *Journal of the Japan landslide society*, **39**(1): 128–136
- Wakai, A. and K. Higuchi 2011 Slope disasters in northern Kanto area induced by the 2011's Off the Pacific Coast of Tohoku Earthquake (part 1). Proc. 50th Congress of Japan landslide society, pp. 5–6