Several Characteristics of Hydraulic Jump Controlled by the Subdam

Kato, Osamu

Laboratory of Land-Drainage and Reclamation, Faculty of Agriculture, Kyushu University

Tanaka, Kohei

Laboratory of Land-Drainage and Reclamation, Faculty of Agriculture, Kyushu University

Tohara, Yoshio

Laboratory of Land-Drainage and Reclamation, Faculty of Agriculture, Kyushu University

Hasegawa, Koichi

Laboratory of Land-Drainage and Reclamation, Faculty of Agriculture, Kyushu University

他

<https://doi.org/10.5109/23494>

出版情報：九州大学大学院農学研究院紀要. 21 (2/3), pp.141-152, 1977-03. Kyushu University
バージョン：
権利関係：

Several Characteristics of Hydraulic Jump Controlled by the Subdam

**Osamu Kato*, Kohei Tanaka, Yoshio Tohara*,
Koichi Hasegawa and Itaru Uesato**

Laboratory of Land-Drainage and Reclamation, Faculty
of Agriculture, Kyushu University 46-05, Fukuoka 812

(Received December 15, 1976)

Water stored in a dam has far larger potential energy than the flow-water in river before banking. So, it is important to dissipate energy in water flowing over dam, chute and other hydraulic structures and thus prevent scouring downstream from structures. From a practical viewpoint, hydraulic jump is a useful means of dissipating the energy. The hydraulic jump used for energy dissipation is usually confined to the stilling basin. Furthermore, in order to control the jump, the accessories are usually installed in the basin to shorten the range in which the jump will take place. In this investigation, subdam was used as accessory to control the jump. The objective of this study was to investigate the methods for determining the height of subdam, its setting place, and its downstream depth.

1 THEORETICAL ANALYSIS

Methods for determining the height of subdam

According to Iwasaki (1961), the height of subdam is theoretically represented in the following equation:

$$\frac{d}{h_1} = \frac{(1+2F^2)\sqrt{1+8F^2}-1-5F^2}{1+4F^2-\sqrt{1+8F^2}} - \frac{3}{2}F^3 \quad (1)$$

where h_1 is the depth at the beginning point of a jump, d is the height of subdam and $F(=v_1/\sqrt{gh})$ is the Froude number using the mean velocity (v_1) at the beginning point of a jump (the toe of the roller).

This equation is derived from the following assumptions:

- (i) the momentum is conserved between sections I and II in Fig. 1,
- (ii) energy losses are negligible between sections II and III,
- (iii) the critical depth occurs on the subdam.

According to the assumption (i), the following equation is obtained;

$$\frac{h_2}{h_1} = \frac{1}{2} \left(\sqrt{1+8F^2} - 1 \right) \quad (2)$$

From the assumption (ii) and the application of the Bernoulli's theorem to the flow between sections II and III, the following relation is derived:

* Present address: Laboratory of Land-Improvement, Faculty of Agriculture, Saga University, Saga 840

Fig. 1. Definition sketch.

$$\frac{v_2^2}{2g} + h_2 = \frac{v_3^2}{2g} + (h_c + d) \quad (3)$$

where v_2 and v_3 are the mean velocity at sections II and III, respectively, h_2 is the water depth at section II and $h_c (=h_3)$ is the critical water depth at section III. From Eqs. (2) and (3), Eq. (1) is obtained.

According to assumption that energy losses between sections II and III would be the function of overflow-coefficient of the weir, Forster and Skrinde (1950) suggested the following equation;

$$\begin{aligned} N^2 + N = & 0.664(N-r)^3 \left[0.770 + 0.847 \left(\frac{N-r}{N} \right)^2 + 0.234 \left(\frac{N-r}{N} \right)^4 + 0.225 \left(\frac{r}{N-r} \right) \right. \\ & + 0.248 \frac{r}{N} \left(\frac{N-r}{N} \right) + 0.068 \left(\frac{N-r}{N} \right)^3 \times \frac{r}{N} + 0.016 \left(\frac{r}{N-r} \right)^2 + 0.018 \left(\frac{r}{N} \right)^2 \\ & \left. + 0.005 \left(\frac{N-r}{N} \right)^2 \times \left(\frac{r}{N} \right)^2 \right] \end{aligned} \quad (4)$$

where $N = h_2/h_1 = \frac{1}{2}(\sqrt{1+8F^2}-1)$ and $r = d/h_1$. By applying the law of momentum conservation to the flow between sections II and III, the following equation is obtained :

$$\frac{d}{h_1} = \frac{1}{2}(\sqrt{1+8F^2}-1) - \left(\frac{1}{2}(1+4F^2 - \sqrt{1+8F^2}) + 3F^{\frac{4}{3}} - 2F^2 - 1 \right)^{\frac{1}{2}} \quad (5)$$

Figure 2 shows the comparison of Eqs. (1), (4) and (5).

Considering the external forces that act on the water by subdam in a jump, the following equation is obtained (see Fig. 3) :

$$\frac{q}{g}(v_1 - v_2) = \frac{1}{2}(h_2^2 - h_1^2) + \frac{P_x}{w} \quad (6)$$

where q is the discharge per unit width of the channel, v_1 and v_2 are the mean velocity at sections I and II, respectively, h_1 is the depth of the beginning point of a jump, h_2 is the downstream depth of subdam, w is the specific weight of water and P_x is the external forces that act on the water in a jump. Substituting $C_p = h_2/h_1$, $\lambda = F^2 = q^2/g h_1^3$ and $R_x = P_x / \frac{w h_1^2}{2}$ to Eq. (6),

$$C_p - (2\lambda + 1 - R_x)C_p + 2\lambda = 0 \quad (7)$$

Fig. 2. Variation of relative height of subdam with F .

Fig. 3. Definition sketch.

When X is assumed as the distance from the beginning point of a jump, the depth (h) at the front of subdam will be given by the following equation;

$$h = \left\{ 1 + \left(\frac{X}{L} \right) (N-1) \right\} h_1 \quad (8)$$

where $N = h_j/h_1 = \frac{1}{2} (\sqrt{1+8F^2} - 1)$, h_j is the conjugate depth to h , and L is the length of the roller. The depth (h) does not, however, change linearly in practice, so that Eq. (8) should be corrected as follows:

$$h = k h_1 = C_R \left\{ 1 + \left(\frac{X}{L} \right) (N-1) \right\} h_1 \quad (9)$$

$$k = C_R \left\{ 1 + \left(\frac{X}{L} \right) (N-1) \right\} \quad (10)$$

where C_R is the correction-coefficient. From Eq. (9), the mean velocity (v) at the section X is

$$v = v_1 / k \quad (11)$$

As the total dynamic water pressure acting on the front of subdam is generally given by the expression;

$$C_D \rho v^2 d / 2$$

(C_D : coefficient of drag), the following equation is obtained by using Eq. (11);

$$C_D w \lambda h_1 d / 2k^2 \quad (12)$$

The hydrostatic pressures acting on the front and the back of subdam are

$$wd(kh_1 - d/2) \quad (13)$$

and

$$-wd(k'h_1 - d/2) \quad (14)$$

respectively, where k' is the ratio of a real depth to a theoretical conjugate depth (h_1) to h_1 . From Eqs. (12), (13) and (14),

$$R_x = P_x / \frac{wh_1^2}{2} = [C_D w \lambda h_1 d / 2k^2 + wd(kh_1 - d/2) - wd(k'h_1 - d/2)] / \frac{wh_1^2}{2} \\ = m' (C_D \lambda / k^2 + 2k - 2k'N) \quad (15)$$

where $m' = d/h_1$ and $N = h_1/h_1$. Substituting Eq. (15) to Eq. (7),

$$C_p^3 - [2\lambda + 1 - m' (C_D \lambda / k^2 + 2k - 2k'N)] C_p + 2\lambda = 0 \quad (16)$$

According to Eq. (16), the depth (h_1) is deduced from the experimental values of C_D , k and k' .

Method for determining the setting place of the subdam

The results of Ralph's experiments (1950) have shown that the forces acting on the subdam in a jump decrease rapidly to a minimum as the downstream end of the jump is moved upstream a position approximately over the subdam (see Fig. 4). Then the force increases slowly to a constant value as the jump is moved farther the upstream. From the facts described above, it could be estimated that the distance between the beginning point of a jump and the subdam should be approximately equal to the length of the jump. But the length of a jump is not predicted. Therefore, the following experimental

Fig. 4. Force on the subdam at various positions of the subdam (by Ralph, 1950).

expression by Bakhmeteff and Matzke (1938) must be relied on to have a useful design ;

$$X = (4.5-5) h, \quad (17)$$

where X is the distance between the beginning point of a jump and the subdam;

and h_1 is the conjugate depth to the beginning depth of a jump.

Jump in sloping channels

Common forms of the hydraulic jump in sloping channels have been classified into four general cases as shown in Fig. 5 (Kindsvater, 1944).

Case 1, with the entire on the horizontal floor, is the jump in horizontal channel. Case 2 is the jump with the toe of the roller on the slope and the end of the roller on the horizontal floor. Case 3 is the jump with the toe of the roller on the slope and the end at the junction of the sloping and horizontal floor. Case 4 is the jump with the entire roller on the slope.

Fig. 5. Basic cases of the hydraulic jump in sloping channels.

In case 1, Eq. (1) is applicable. Case 2 is intermediate between cases 1 and 3, but either the theory of case 1 or that of case 3 is not applicable to this case. It is proved from the experimental results that case 3 can be dealt with the same pattern as case 4. Case 3 is analyzed theoretically as follows.

Fig. 6. Elements of a hydraulic jump.

Figure 6 shows case 3 with slope angle θ . In Fig. 6, $v_1 \cos \theta$ is the horizontal component of the average velocity in section I at the toe of the jump, and v_1 is the average velocity in section II at the end of the jump. By applying the law of momentum conservation between sections I and II, the following equations are given for the horizontal direction,

$$\frac{w}{g} q(v_2 - v_1 \cos \theta) = P_1 \cos \theta - P_2 + P_s \sin \theta \quad (18)$$

and for the vertical direction,

$$\frac{w}{g} q v_1 \sin \theta = P_s \cos \theta - p_s \sin \theta \quad (19)$$

where P_1 and P_2 are the static pressure in section I ($=w/2 \cdot h_1^2 \cos \theta$) and in section II ($=w/2 \cdot h_2^2$), respectively. P_s is the static pressure acting on the slope between sections I and II given as follows:

$$P_s = \frac{w}{2} \left\{ h_1^2 \tan \theta + l_j \left(\frac{h_1}{\cos \theta} + h_2 \right) \right\}$$

From Eqs. (18), (19), the continuity equation : $h_1 v_1 = h_2 v_2$ and $F = v_1 / \sqrt{g h_1}$,

$$h_2^3 - (h_1^2 + 2 \sec \theta F^2 h_1^2) h_2 + 2 F^2 h_1^3 = 0 \quad (20)$$

Letting N be $N = h_2/h_1$, Eq. (20) becomes

$$N^3 - (1 + 2 \sec \theta F^2) N + 2 F^2 = 0 \quad (21)$$

In the case of $\theta = 0$, Eq. (21) reduces to

$$N^3 - (1 + 2 F^2) N + 2 F^2 = 0$$

A root of this equation is $N = \frac{1}{2}(\sqrt{1 + 8 F^2} - 1)$, which is identical with Eq. (2). Figure 7 which shows the relations between N and F is respected by Eq. (21) using θ parameter.

Fig. 7. Relation between N and F (Eq. 21).

Energy losses in hydraulic jump

By applying Bernoulli's theorem to the flow between sections I and II (see Fig. 6), the following relation is given;

$$l_j \tan \theta + h_1 \cos \theta + \frac{v_1^2}{2g} = h_2 + \frac{v_2^2}{2g} + I_s \quad (22)$$

where I_s is the specific energy loss.

From the continuity equation $v_1 h_1 = v_2 h_2$, Eq. (22) becomes

$$I_s = \frac{h_1}{2} F^2 \left(1 - \frac{1}{N^2} \right) + h_1 (\cos \theta - N) + l_j \tan \theta \quad (23)$$

where $N = h_2/h_1$. From Eq. (21) and $i_s = I_s/h_1$, Eq. (23) becomes

$$i_s = \frac{(N^2 - 1)^2}{4N(N \sec \theta - 1)} + \cos \theta - N + \frac{l_j}{h_1} \tan \theta \quad (24)$$

For $\theta=0$, **Eq. (24)** reduces to

$$I_{g0} = \frac{(N-1)^3}{4N} \quad (25)$$

A better expression of energy loss in the jump is obtained by expressing it as percentage of the initial energy. From Fig. 6,

$$\% \text{ loss} = E = \frac{100 I_g}{I_j \tan \theta + h_1 \cos \theta + \frac{v_1^2}{2g}} \quad (26)$$

Using **Eqs. (23)** and (21),

$$E = \frac{4(I_j/h_1 \cdot \tan \theta + \cos \theta - N)N(N \sec \theta - 1) + (N^2 - 1)^2}{4(I_j/h_1 \cdot \tan \theta + \cos \theta)N(N \sec \theta - 1) + N^2(N^2 - 1)} \times 100 \quad (27)$$

For $\theta=0$, **Eq. (27)** reduces to

$$E_0 = \frac{(N-1)^3}{N(N^2 + N + 4)} \times 100 \quad (28)$$

2 EXPERIMENTAL ARRANGEMENT

Experimental equipment was the model (reduced to a scale of 1/50) of the spillway attached to Gōsho-dam (in Ukiha-Machi, Fukuoka Pref.). The equipment is shown in Figs. 8-10. The inlet was fan-shaped. Chute was a rectangular flume 54.2 cm wide (27.1 m in prototype). From now on, the values in parentheses mean the dimension of the prototype). Slope of chute was 1 on 2. A height between the inlet floor and the stilling basin floor was 114.8 cm (57.4 m). The design floor discharge of this spill-way was $Q=49.8 \text{ l/sec}$ ($880 \text{ m}^3/\text{sec}$). For this discharge (Q), the depth at the beginning of a jump was $h_1=1.9 \text{ cm}$ (0.942 m). By applying Iwasaki formula (**Eq. 1**), the height of subdam was given with $d=15.6 \text{ cm}$ (7.8 m), and then from **Eq. (17)** the length of stilling basin was obtained with $X=144 \text{ cm}$ (72 m). Referring to these values, experi-

Fig. 8. Arrangement of experimental apparatus.

Fig. 9. Experimental apparatus (cm).

Fig. 10. Experimental apparatus (cm).

Table 1. Experimental details.

X cm	d cm	v_1 cm/s	h_1 cm	F	Run
144	15.6	350			1
		385	1.01	11.12	
			1.5%	9.78	
		400	1.82	9.47	
		409	2.23	8.75	
		421	2.39	8.70	
144	17.2	329	0.75	12.14	2
		37%	1.59	9.60	
		404	1.99	9.15	
		410	2.40	8.45	
		421	2.70	8.1%	
144	1% .9	336	0.84	11.71	3
		381	1.39	10.32	
		390	1.81	9.26	
		411	2.41	8.25	
		415	2.5%	8.25	
134	1% .9	33%	0.86	11.64	4
		386	1.44	10.2%	
		400	1.74	9.69	
		411	2.26	8.55	
		415	2.52	8.35	
124	15.6	341	0.91	11.42	5
		395	1.47	10.41	
		39%	1.94	9.13	
		409	2.39	8.45	
		414	2.75	7.97	

ments were carried out under the conditions as shown in Table 1.

As the water depth was measured with manometers, the values of the observed water depth have been found higher than the measured ones because of air mixing. The velocity distributions were measured with small sized current meters and pitot tubes, and the discharge was measured with a square weir equipped at the end of the channel.

3 EXPERIMENTAL RESULTS

Height of subdam

Figure 2 shows that the measured relative heights (d/h_1) are larger than calculated ones by Eqs. (1), (4) and (5). This fact may be caused by the backwater due to the contraction of downstream-channel in the experiments. The selection of subdam height needs being considered the backwater into Eqs. (1), (4) and (5).

Conjugate depth

Photograph 1 shows that the jump begins in the chute, so that N in Eq. (21) instead of N in Eq. (9) should be used to calculate the depth (h_2) at the downstream of the subdam from Eq. (16). Figures 11 and 12 show k in Eq. (9) as a function of X/l_j and k' in Eq. (14) as a function of X/h_1 respectively. Figure 13 shows a comparison of measured and calculated values from Eq. (16),

Photo. 1. Hydraulic jump in sloping channels.

Fig. 11. Variation of k with (X/Z) .

Fig. 12. Variation of k' with (X/h) .

Fig. 13. Comparison of measured and calculated values.

using above results. In Fig. 13, the measured values are larger than the calculated ones. This may be attributed to the backwater due to the contraction of downstream channel.

Energy losses due to a jump in slope

When the toe of the roller is on the slope, the relation between l_j/h_1 and F is shown in Fig. 14, that is;

$$\frac{l_j}{h_1} = 0.305 \times 10^{0.185F} \quad (29)$$

where l_j is a horizontal distance from the toe of the jump to a junction of the sloping and horizontal floors, h_1 is a water depth at the toe of the jump, and F

Fig. 14. Relation between (l_j/h_1) and F .

Fig. 15. Energy losses in hydraulic jump; i_g .

Fig. 16. Energy losses in terms of N .

is Froude number. Substituting Eq. (29) in Eqs. (24) and (27), values of i_g and E are given in Figs. 15 (a), 15 (b), 16 (a) and 16 (b). In our experiments, $i_g = 25 \sim 180$, $E = 60 \sim 85$ %.

CONCLUSION

1. In this paper, three methods used for determining the height of subdam were introduced, those are Iwasaki formula, Forster and Skrinde formula and a formula derived from a law of momentum conservation. But, there were no remarkable differences. Therefore, for the field planning, Iwasaki formula being relatively simple can be applied to determine the height of subdam.

2. Distance from the junction of the sloping and horizontal floors to subdam can be available about 5 times the conjugate depth (=the length of a jump).

3. The downstream depth of subdam calculated from Eq. (16), has two constant values, k and k' , determined by experiments. Therefore, more detailed experiments should be carried out in order to obtain values of k and k' .

REFERENCES

- Bakhmeteff, B. A. and Matzke 1938 The hydraulic jump in terms of dynamic similarity. *Trans. A.S.C.E.*, 101: 603-647
- Forster, J. W. and R. A. Skrinde 1950 Control of the hydraulic jump by sills. *Trans. A.S.C.E.*, 115: 973-987
- Iwasaki, T. 1961 On the energy dissipator of the spillway, *Proc. Tohoku-Branch, Japan. Soc. Civil Engineers*, (in Japanese), p. 62
- Kindsvater, C. E. 1944 The hydraulic jump in sloping channels. *Trans. A.S.C.E.*, 109: 1107-1154
- Ralph, M. W. 1950 Discussion on control of the hydraulic jump by sills, by J. W. Forster and R. A. Skrinde. *Trans. A.S.C.E.*, 115: 1003-1006