

ミキシング コンソール ガ スタジオ ノ オンキョウ
トクセイ ニ アタエル エイキョウ

中原, 雅考

<https://doi.org/10.15017/458907>

出版情報 : Kyushu University, 2004, 博士 (芸術工学) , 課程博士
バージョン :
権利関係 :



参考文献

References

- [1] M. Nakahara, A. Omoto, K. Fujiwara, "Scattering Effect of a Mixing Console in a Production Studio," Proc. International Symposium on Room Acoustics: Design and Science (RADS), 050 (2004)
- [2] P. H. Heringa, K. Rijk, "Design of small control rooms with broadband frequency response," Proc. AES 84th Convention, Paris, 10, 11-2631(K-5) (1988)
- [3] P. R. Newell, *Project Studios: A More Professional Approach*, Focal Press, e.g., 61-84, 146-195(2000)
- [4] M. Nakahara, A. Omoto, "Room acoustic design for small multichannel studios," Proc. AES 24th International Conference on Multichannel Audio, Banff, 319-334 (2003)
- [5] 忠平好生, 高島和博, 鶴秀男, 福満英章, 崎山安洋, 清水利夫: スタジオ調整室の音場解析-(2)数値計算によるアプローチ. 日本音響学会講演論文集, 913-914(1997.9)
- [6] *Multichannel stereophonic sound system with and without accompanying pictures*, Recommendation ITU-R BS. 775-1, 3 (1992-1994)
- [7] *Method for the subjective assessment of small impairments in audio systems including multichannel sound systems*, Recommendation ITU-R BS. 1116-1, 16-20 (1994-1997)
- [8] *Recommendations for surround sound production*, Producers & engineering wing surround sound recommendations committee, The national academy of recording arts & science, Inc., 3-6 (2004)
- [9] K. Mimoto, T. Wakatsuki, M. Sawaguchi, "Multi-channel Sound Control Room in NHK - Design policy and guideline," Proc. AES 19th International Conference on Surround Sound, Schloss Elmau, 105-110 (2003)
- [10] R. Seznec, "Diffraction of sound around barriers: use of the boundary elements technique," Journal of Sound and Vibration, 73(2), 195-209 (1980)
- [11] 大久保朝直: ソフトな円筒エッジを持つ防音壁の遮音性能に関する研究. 九州芸術工科大学博士論文, 41-46(1998)
- [12] H. A. Scheck, "Improved Integral Formulation for Acoustics Radiation Problems," Journal of Acoustical Society of America, 44, 41-58 (1968)

- [13] A. J. Burton, G. F. Miller, "The application of integral equation method to the numerical solutions of some exterior boundary value problem," Proc. Royal Society of London, A323, 201-210 (1968)
- [14] S. A. Young, "A boundary integral equation for two-dimensional acoustic scattering problems," Journal of Acoustical Society of America, 105, 93-105 (1999)
- [15] 石塚崇, 藤原恭司:境界要素法を用いた防音壁遮音性能の解析における計算誤差改善に関する研究. 日本音響学会講演論文集, 829-830(2003.9)
- [16] 石塚崇:特殊エッジ形状を持つ防音壁の遮音性能に関する研究. 九州芸術工科大学博士論文, 45-59(2003)
- [17] 鈴木陽一, 浅野太, 金学胤, 曾根敏夫:時間引き伸ばしパルス of 設計法に関する考察. 信学技報, EA92-86, 17-24(1992)
- [18] 前出 [11], 47-57(1998)
- [19] 前出 [11], 19-23(1998)
- [20] 前出 [15], 7-19, 40-44, 143-148(2003)
- [21] C. Kai, A. Ikeda, S. Ueoka, M. Nakahara, A. Omoto, "Acoustic design of a multichannel production Studio: Example of a small/medium post-production studio in Tokyo," Proc. International Symposium on Room Acoustics: Design and Science (RADS), 055(2004)
- [22] A. Ikeda, M. Nakahara, C. Kai, A. Omoto, "The acoustical effect of audio equipment and furniture in a mixing room," Acoustical Science and Technology, (2005.3 掲載予定)
- [23] 中原雅考, 尾本章, 藤原恭司:ミキシングコンソールがスタジオのリスニング特性に与える影響. 日本音響学会講演論文集, 967-968(2004.9)
- [24] M. Nakahara, A. Omoto, K. Fujiwara, "The effect of a mixing console on the monitoring response in a mixing room," Acoustical Science and Technology, (2005.3 掲載予定)